

R300 EQUIPMENT SPECIFICATIONS

BOARDS	weight	length	width	volume	cb	fin
Phantom 295 L	13.25	295	72	217	78	DT 54
RS:One	14	300	80	211	63	PB 48
SG 272 Sportsman	13	272	80	220	63	DT 56
T293 OD	13	292	79	205	60	DT 46/50

SAILS	size	size	size	battens	cams
Phantom 295 Race	6.5			6	2
Phantom 295 Race		7.5	8.5	7	3
RS:One	6.5	7.8		6	2
RS:X			8.5	8	3
SG Race	6.5	7.5		6	2
SG Race			8.5	7	3
T293 OD	6.8	7.8	8.5	6	2

MASTS	length	length	length	carbon%
Phantom 295	430	460	490	75
RS:One		460		60
NP			490	60
SG272	460	460	490	80
T293	460	460	490	60

BOOMS	size	size	size
Phantom 295	190>240	220>250	220>250
RS:One		200>250	
SG272	200>240	200>240	240>280
T293	185>235	185>235	205>255

Criteria for inclusion on the Approved List

Key features - durability, low cost, availability

Full carbon composite hulls are not permitted

Centreboards - only cb supplied with the hull may be used

Fins are interchangeable between hulls; DT -deep tuttle (2 bolts); PB- power box (1 bolt)

Sails - maximum 8 battens and 3 cams

Masts - maximum 80% carbon content

Booms - aluminium, carbon booms not permitted

Mast extensions - any aluminium extension, including std supplied with branded rigs